



Sloan Hydraulic Drop Arm Barrier (M50/P2)

ITEM: #HD-8050



PRODUCT FEATURES

A Proven Design in Crash Protection.

Sloan's Hydraulic Drop Arm Barrier is known for its reliability, engineering and proven design. Featuring a pivoting drop-arm mechanism, it provides efficient traffic management and effective crash-protection.

- ASTM F2656-07 M50/P2 Certified
- Hydraulic Deployment
- Multiple Arm Widths (12' - 24')
- Hot-Dip Galvanize or Color Coat

PRODUCT BENEFITS

Precision and Reliability at its Best.



Climate Resilient

Designed with heated posts, our drop arm can operate in a variety of conditions, guaranteeing reliable performance no matter where you are in the world.



Custom Lengths

Customizable sizing for our drop arm allows for a precise fit the specific dimensions of your space or application.



Rapid Deployment

With a 6-8 second open/close rate, you can ensure effective deployment for high-risk areas or emergency situations.



Sloan Hydraulic Drop Arm Barrier (M50/P2)

ITEM: #HD-8050

VEHICLES BELOW SUBJECT TO SEARCH
PROHIBITED FROM ENTERING UNAUTHORIZED
AND HAZARDOUS SUBSTANCES
EQUIPMENT, MEDIA TRANSMITTING AND
MATERIAL FOUND IN THE POSSESSION OF
VEHICLE WHILE TRANSITING INSTALLATION.
VEHICLES ARE PROHIBITED FROM RETURNING AND
ON FARRINGTON HIGHWAY, AND
IT GRANTING ACCESS TO THE KUAOKALA
COURT WHILE ON INSTALLATION
YOU ARE SUBJECT TO CRIMINAL
PENALTIES AS APPLICABLE
31-320, 31-107, 31-240, and pending directives



CERTIFICATIONS

Crash-Rated

Crash tested and certified by the Department of Defense (DoD) with an ASTM F2656-07 M50/P2 rating (K12).

Capable of halting a 15,000 lb. vehicle traveling at 50 mph.

M50/P2 (K12)



Specifications

Item #	HD-8050
Crash-Rating	ASTM F2656-07 M50/P2
Model	Hydraulic
Finish	Galvanized
Open/Close Time	6 to 8 seconds
Foundation Depth	4'
Widths	12' - 24'
Warranty	5 year

Product Options

- Custom Arm Sizes
- Heated Pivot & Catch Post
- Custom Finish Colors
- Biodegradable Fluid



Download a full list of specs at WWW.SLOANSG.COM/HD-8050

