



# Sloan Hydraulic Drop Arm Barrier (M30/P1)

ITEM: #HD-8030



## PRODUCT FEATURES

### High-Performance Crash Protection.

Sloan's M30 Hydraulic Drop Arm Barrier is known for its dependable pivoting mechanism that delivers high-performance operation, efficient deployment time, and a climate resilient design.

- ASTM F2656-07 M30/P1 Certified
- Hydraulic Deployment
- Multiple Arm Widths (12' - 24')
- Hot-Dip Galvanize or Color Coat

## PRODUCT BENEFITS

### Optimal Precision and Reliability.



#### Climate Resilient

Designed with heated posts, our drop arm can operate in a variety of conditions, guaranteeing reliable performance no matter where you are in the world.



#### Custom Lengths

Customizable sizing for our drop arm allows for a precise fit the specific dimensions of your space or application.



#### Rapid Deployment

With a 6-8 second open/close rate, you can ensure effective deployment for high-risk areas or emergency situations.



# Sloan Hydraulic Drop Arm Barrier (M30/P1)

ITEM: #HD-8030



## CERTIFICATIONS

### Crash-Rated

Crash tested and certified by the Department of Defense (DoD) with an ASTM F2656-07 M30/P1 rating (K4).

Capable of halting a 15,000 lb. vehicle traveling at 30 mph.

### M30/P1 (K4)



## Specifications

Item #	HD-8030
Crash-Rating	ASTM F2656-07 M30/P1
Model	Hydraulic
Finish	Galvanized
Open/Close Time	6 to 8 seconds
Foundation Depth	48"
Widths	12' - 24'
Warranty	5 year

## Product Options

- Custom Arm Sizes
- Heated Pivot & Catch Post
- Custom Finish Colors
- Biodegradable Fluid



Download a full list of specs at  
[WWW.SLOANSG.COM/HD-8030](http://WWW.SLOANSG.COM/HD-8030)

